

General Description

MB Series Melt Blown filter cartridge are made from 100% FDA complied Polypropylene material. They are manufactured through thermal bonding technology with graded density structure for better filter efficiency and dirt holding capacity. MB series are suitable for wide range of filtration applications and fit well in most of the standard filter housings in the market. .

Features

- ❖ Continuously graded pore structure
- ❖ High dirt holding capacity
- ❖ Suitable for all industrial filter housing
- ❖ Reliable and consistent filtration



Application

- ❖ Food & Beverages processing
- ❖ Portable Water Systems
- ❖ Metal Finishing / Plating Solutions
- ❖ Solvent Filtration
- ❖ Reverse Osmosis Pre-treatment

Specification

Micron Rating : 0.5 – 50 micron
 Max. Pressure : 50 psid (3.4 bar) @ 70°C
 Max. Temperature : PP=60°C,
 Standard Core Dia. : 1.1" (28mm) nominal
 Available in lengths 10" - 40 inches

Ordering Information

Filter Media	Rating	Width	Length	End Cap
MB = Polypropylene	0.5	R = 2.5" T = 4.5"	10 = 10"	0: DOE 1: Close End 2: 222/ Flat 3: 222/ Fin
	1		20 = 20"	
	3		30 = 30"	
	5		40 = 40"	
	10			
	25			
	50			